

TECHNICAL DATA SHEET

MULTI FUNCTION TIMER – D1 ETM1



Supply Voltage : 12 VDC ± 20%
Aux. Voltage : 24 V AC/DC ± 20%
 : *24-240V AC/DC +10%,-20%
 : *100-120/220-240/380-440V AC ± 20%

Output Contact : **1 CO + 1 CO**

Time Range : 0.1-1, 1- 10, 6 - 60, 60-600 seconds
 : 0.1- 1, 1-10, 10-100 hours

Operating Modes :

M1 - On delay
 M2 - Interval
 M3 - Cyclic off first
 M4 - Cyclic on first
 M5 - Star Delta *
 M6 - Instant and Delayed
 M7 - Engine Start Mode

} Selectable By Rotary Switch

Weight : 200 gms.

Dimensions (mm)

Over All (LxWxD) : 76 x 30.5 x 117.5
Mounting (L xW) : 68 centre to centre/ 35 mm rail Mounting

Note : Wherever not specified Contact Rating: 5A @ 230 V AC (resistive)
 * : CE / CSA not available for 110V AC & 24-240V AC/DC models.

Minilec India Pvt. Ltd.

S.No. 1073/1-2-3, At Post : Pirangoot, Tal : Mulshi, Dist : Pune (India), Pin : 412 111
 Tel : (020) 22922162 / 22922354-57. Fax : (020) 22922134 or (020) 25432349 / 25431573.
 Website : <http://www.minilecgroup.com> E-Mail : mkt1@minilecgroup.com

