

## TECHNICAL DATA SHEET MULTI FUNCTION TIMER – S2 ETM1



**Supply Voltage** : 12 VDC ± 20%  
**Aux. Voltage** : 24 V AC/DC ± 20%  
 : \*24-240V AC/DC +10%, -20%  
 : \*100-120/220-240/380-440V AC ± 20%

**Output Contact** : 1 CO + 1 CO

**Time Range** : 0.1-1, 1-10, 6-60, 60-600 seconds  
 : 0.1-1, 1-10, 10-100 hours

**Operating Modes** :

M1 - On delay  
 M2 - Interval  
 M3 - Cyclic off first  
 M4 - Cyclic on first  
 M5 - Star Delta \*  
 M6 - Instant and Delayed  
 M7 - Engine Start Mode

Selectable By Rotary Switch

**Weight** : 150 gms.

**Dimensions (mm)**

**Over All (LXWXD)** : 90 x 35 x 60  
**Mounting (L x W)** : 35 mm rail Mounting

**Note** : Wherever not specified Contact Rating: 5A @ 230 V AC (resistive)

\* : CE / CSA not available for 110V AC models.

### Minilec India Pvt. Ltd.

S.No. 1073/1-2-3, At Post : Pirangoot, Tal : Mulshi, Dist : Pune (India), Pin : 412 111  
 Tel : (020) 22922162 / 22922354-57. Fax : (020) 22922134 or (020) 25432349 / 25431573.  
 Website : <http://www.minilecgroup.com> E-Mail : [mkt1@minilecgroup.com](mailto:mkt1@minilecgroup.com)