

TECHNICAL DATA SHEET

CURRENT MONITORING RELAY – OCS D1



Supply Voltage

System Supply : 110-120/220-240/380-440 V Ac \pm 20%,
Auxiliary Supply : 110/220/230/240/380/415 VAC, + 20%, 12 V DC/24/30 V DC \pm 10%

Ext. Input : 1 Amp / 5 Amp CT (Secondary) or 250 / 500 mA

Trip Setting

Under Current : **N.A.**
Over Current : 50% -140% (adjustable) of CT sec

Trip Time Delay : 1-10 Sec (adjustable)

Power On Delay : 3.5 secs \pm 1.5 sec (fixed)

Resetting Mode : Auto

Output Contacts : 1 CO

Dimensions (mm)

Over All (LxWxD) : 76 x 30.5 x 117.5
Mounting (L xW) : 68 centre to centre/ 35 mm rail Mounting

Wherever not specified
Contact Rating: 5A @ 230 V AC (resistive)

Minilec India Pvt. Ltd.

S.No. 1073/1-2-3, At Post : Pirangoot, Tal : Mulshi, Dist : Pune (India), Pin : 412 111
Tel : (020) 22922162 / 22922354-57. Fax : (020) 22922134 or (020) 25432349 / 25431573.
Website : <http://www.minilecgroup.com> E-Mail : mkt1@minilecgroup.com