

TECHNICAL DATA SHEET

REVERSE POWER RELAY [3 Ph - 3 W] -RPT D2



Supply Voltage

System Supply : 100-120 / 220-240 / 380-440 V AC \pm 20%
Auxiliary Supply : Built in

Ext. Input : 5A CT Secondary & R, Y, B

Output Contact : 2 CO
Trip Setting

Reverse Power : 2% - 20% (adjustable)

Trip Time Delay : 1 - 10 Sec.(Adjustable)

Power On Delay : 1 - 10 Sec. (Adjustable)

Resetting Mode : Auto / Manual

Dimensions (mm)

Over All (LXWXD) : 76 x 56.5 x 117.5 mm

Mounting (LXW) : 67 x 46 / 35 mm rail Mounting

Weight : **460 gms**

Wherever not specified
Contact Rating: 5A @ 230 V AC (resistive)

Minilec India Pvt. Ltd.

S.No. 1073/1-2-3, At Post : Pirangoot, Tal : Mulshi, Dist : Pune (India), Pin : 412 111
Tel : (020) 22922162 / 22922354-57. Fax : (020) 22922134 or (020) 25432349 / 25431573.
Website : <http://www.minilecgroup.com> E-Mail : mkt1@minilecgroup.com