


TECHNICAL DATA SHEET

VOLTAGE MONITORING RELAY - S2 VMR5



Supply Voltage

System Supply : 100-120/220-240/380-440V AC, -25%+20%, 48-63 Hz

Trip Setting (Volts)

Under Voltage : **Phase- Neutral**
For 380-440V AC- 165-245V AC [Variable]
For 220-240V AC- 95-135V AC (Variable)
For 100-110 V AC- 45-65V AC (Variable)

Over Voltage : **Phase- Neutral**
For 380-440V AC- 230-310V AC [Variable]
For 220-240V AC- 130-170V AC [Variable]
For 100-120V AC- 60-80V AC [Variable]

Trip Time Delay : 1-10 Sec (Variable) UV/OV/NF

Power On Delay : 1-10 Sec (Variable)

Resetting Mode : Auto / Manual

Output Contacts : 1 CO + 1 CO / 2 CO

Dimensions (mm)

Over All (LxWxD) : 90 x 35 x 60
Mounting (L xW) : 35 mm rail Mounting

Wherever not specified
Contact Rating: 5A @ 230 V AC (resistive)

Minilec India Pvt. Ltd.

S.No. 1073/1-2-3, At Post : Pirangoot, Tal : Mulshi, Dist : Pune (India), Pin : 412 111
Tel : (020) 22922162 / 22922354-57. Fax : (020) 22922134 or (020) 25432349 / 25431573.
Website : <http://www.minilecgroup.com> E-Mail : mkt1@minilecgroup.com