

TECHNICAL DATA SHEET

GROUND FAULT MONITORING RELAY –S2 CMR3



Supply Voltage

System Supply : 100-120/220-240/380-440 V AC \pm 20%, 48-63 Hz
Auxiliary Supply : 100-120/220 -240 V AC / 24V DC \pm 20%

Ext. Input : 1 Amp or 5 Amp CBCT (Secondary)

Trip Setting

EF Tripping Setting : 10% - 100% of Rated Current Input (Variable),
(Input through CT of 1AMP or 5AMP Secondary)

Trip Time Delay : 0.1-1.0 Sec (Adjustable)

Power On Delay : 1-10 Sec. (Adjustable)

Resetting Mode : Manual

Output Contacts : 2 CO

Dimensions (mm)

Over All (LXWXD) : 90 x 35 x 60
Mounting (LXW) : 35 mm rail Mounting

Wherever not specified
Contact Rating: 5A @ 230 V AC (resistive)

Minilec India Pvt. Ltd.

S.No. 1073/1-2-3, At Post : Pirangoot, Tal : Mulshi, Dist : Pune (India), Pin : 412 111
Tel : (020) 22922162 / 22922354-57. Fax : (020) 22922134 or (020) 25432349 / 25431573.
Website : <http://www.minilecgroup.com> E-Mail : mkt1@minilecgroup.com