

TECHNICAL DATA SHEET

FREQUENCY MONITORING RELAY –S2 FMR1



Supply Voltage

System Supply : 100-120/220-240/380-440 V AC \pm 20%, 38-72 Hz
Auxiliary Supply : Built in

Ext. Input : N.A.

Trip Setting

UNDER FREQUENCY : 40 Hz - 60 Hz (Variable)
OVER FREQUENCY : 50 Hz- 70Hz. (Variable)

Trip Time Delay : 1 - 10 Sec.(Adjustable) \pm 1 Sec.

Power On Delay : 1 - 10 Sec. (Adjustable) \pm 1 Sec.

Resetting Mode : Auto

Output Contacts : 1 CO + 1 CO

Dimensions (mm)

Over All (LXWXD) : 76 x 30.5 x 117.5

Mounting (LXW) : 68 centre to centre / 35 mm Rail Mounting

Wherever not specified
Contact Rating: 5A @ 230 V AC (resistive)

Minilec India Pvt. Ltd.

S.No. 1073/1-2-3, At Post : Pirangoot, Tal : Mulshi, Dist : Pune (India), Pin : 412 111
Tel : (020) 22922162 / 22922354-57. Fax : (020) 22922134 or (020) 25432349 / 25431573.
Website : <http://www.minilecgroup.com> E-Mail : mkt1@minilecgroup.com