


TECHNICAL DATA SHEET

PHASE FAILURE RELAY- S2 VMR2



Supply Voltage

System Supply : 100-110-120 / 220-230-240 / 380-415-440V AC -25+20%,
48-63 Hz, Selectable by Front Knob

Auxiliary Supply : Built-in from 3-Phase

Trip Setting (Volts)

Phase Sequence : Yes
Phase Unbalance : 10% (Fixed) \pm 10%

Under Voltage : For 380-440V AC +20% Fixed
For 220-240V AC +20% Fixed
For 100-120V AC +20% Fixed

Over Voltage : For 380-440V AC -20% Fixed
For 220-240V AC -20% Fixed
For 100-120V AC -20% Fixed

Trip Time Delay

On Phase Failure/ Unbalance : 2 - 5 Sec. (Fixed). / RP-Instant
On UV/ OV : 2 - 5 Sec. (Fixed)

Resetting Mode : Auto

Output Contacts : 2 CO

Dimensions (mm)

Over All (LXWXD) : 90x 35 x 60
Mounting (L x W) : 35 mm rail Mounting

Wherever not specified

Contact Rating: 5A @ 230 V AC (resistive) * CE marked products available on request.

Minilec India Pvt. Ltd.

S.No. 1073/1-2-3, At Post : Pirangoot, Tal : Mulshi, Dist : Pune (India), Pin : 412 111
Tel : (020) 22922162 / 22922354-57. Fax : (020) 22922134 or (020) 25432349 / 25431573.
Website : <http://www.minilecgroup.com> E-Mail : mkt1@minilecgroup.com