

TECHNICAL DATA SHEET

WINDING PROTECTION RELAYS – S2 WTR1



Supply Voltage

Auxiliary Supply : 12/24V DC/100-120/220-240V AC, 50Hz(60 Hz)±10%

Trip Setting (Volts)

Thermistor Sensor Healthy	40 ohm - 4 K ohm
Thermistor Sensor Trip	4.1 K ohm - 5.5 K ohm
Thermistor Sensor Open	5.6 K ohm and above
Thermistor Sensor Short	0- 39 ohms

Trip Time Delay : Less than 1 secs (Fixed) .

Resetting Mode : Below 1.51 K

Output Contacts : 2 CO

Dimensions (mm)

Over All (LXWXD) : 90 x 35 x 60
Mounting (L x W) : 35 mm rail Mounting

Resetting Mode : Auto / Manual

Wherever not specified

Contact Rating: 5A @ 230 V AC (resistive) * CE marked products available on request.

Minilec India Pvt. Ltd.

S.No. 1073/1-2-3, At Post : Pirangoot, Tal : Mulshi, Dist : Pune (India), Pin : 412 111
Tel : (020) 22922162 / 22922354-57. Fax : (020) 22922134 or (020) 25432349 / 25431573.
Website : <http://www.minilecgroup.com> E-Mail : mkt1@minilecgroup.com